

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
8 January 2004 (08.01.2004)

PCT

(10) International Publication Number  
**WO 2004/004060 A1**

(51) International Patent Classification<sup>7</sup>:  
H05K 5/03

H01P 1/20 //

(74) Agent: MAGNUSSON, Monica; Ericsson AB, Patent  
Unit Radio Access, S-164 80 Stockholm (SE).

(21) International Application Number:

PCT/SE2002/001305

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,  
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,  
VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 28 June 2002 (28.06.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (*for all designated States except US*): TELE-  
FONAKTIEBOLAGET L M ERICSSON (publ)  
[SE/SE]; S-126 25 Stockholm (SE).

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,  
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent  
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,  
NE, SN, TD, TG).

(72) Inventors; and


(75) Inventors/Applicants (*for US only*): HENNINGSSON,  
Uno [SE/SE]; Klingvägen 17, S-136 73 Haninge (SE). LI-  
IKAMAA, Matti [SE/SE]; Arvid Mörmesväg 31, S-168 46  
Bromma (SE). FORSSÉN, Karl-Gösta [SE/SE]; Banvä-  
gen 44, S-175 67 Järfälla (SE).

Published:

— with international search report

[Continued on next page]

(54) Title: INTEGRATED FILTER CONSTRUCTION



(57) Abstract: The present invention relates to an improved and compact filter arrangement and a method for a cost-efficient assembling of such an arrangement. The filter arrangement according to the present invention comprises a cover of the filter chassis that serves both as a mechanical and electrical shielding of the filter chassis and as a carrier of a printed circuit board for electrical components such as the filter chassis and the printed circuit board can refer to the same ground. It is possible to mount additional circuit boards, that are each shielded from each other, from the same direction on said first printed circuit board. The various units are automatically contacted during manufacturing by means of coupling components that connect adjacent units to each other.

WO 2004/004060 A1